



TH2110D1009/U

PRO 2000 Vertical Programmable Thermostats

[Find Equivalent or Replacement Products.](#)

Product Specifications

Application	Heat/Cool or Heat Pump without Auxiliary Heat
Dimensions (in.)	4 11/16 in. High X 2 7/8 in. Wide X 1 1/8 in. Deep
Dimensions (mm)	120 mm high x 74 mm wide x 28 mm deep
Item Type	Product
Mounting	Vertical
Electrical Ratings	20 to 30 Vac or 750 mV
Frequency	50 Hz; 60 Hz
Stages	1 Heat/1 Cool
Tradeline Value	
Operating Humidity Range (% RH)	5 to 90% RH, non-condensing
Switch Positions (System)	HEAT-OFF-COOL
Switch Positions (Fan)	AUTO-ON
Sensor Element	
Accuracy (F)	
Accuracy (C)	
Color	Premier White®
Switch Type	
Programmability	5-2 Day Program
Power Method	Dual Powered: Battery or Hardwire
Terminal Designations	R, C W, Y G, O/B
Display Size	1.73 sq in.
Changeover	Manual
Setting Temperature Range (F)	Heat: 40 to 90 F; Cool: 50 to 99 F
Setting Temperature Range (C)	Heat: 4.5 to 32 C; Cool: 10 to 37 C
Cycles per Hour	Heating 2 - 6 CPH; Cooling 2 -6 CPH
Cool Current	0.02 A to 1.0 A running
Heat Current	0.02 A to 1.0 A running