T22U115B

standard with fan

> CONTACT US



T series roof exhaust units represents an optimal solution for heat dissipation through the top of electrical cabinets. They are ideal for indoor use where there is limited space on the front and side panels. According to the ambient conditions these units can operated with fan (forced air) or without a fan (natural air convection).

Technical data		
APPROVALS		
Approvals	CE; UKCA	
PERFORMANCE		
Max Airflow	800/850	m³/h
	471/500	CFM
Airflow with Exhaust Filter	660/700	m³/h
	388/412	CFM
Max Static Pressure	435/548	Pa
	1.75/2.20	in H2O
ELECTRICAL DATA		
Rated Voltage	115	V a.c.
Rated Current	1.1/1.5	А
Rated Power	130/170	W
Operating Voltage	103.5-126.5	V a.c.
Frequency	50/60	Hz
Appliance Class	I	
Motor Protection	Thermally Protected	
GENERIC DATA		
RAL Number	7035	
Electrical Connection	Wires	
Life Expectancy	70000	h at 25 °C
	70000	h at 77 °F



T22U115B standard with fan

> CONTACT US


Technical data			
Wires Section	1	mm²	
Fan Noise	74/75.6	dB(A)	
ENVIRONMENTAL AND THERMAL DATA			
IP Protection Degree	IP23		
Operating Temperature	-20÷60	°C	
	-4÷140	°F	
Storage Temperature	-30÷70	°C	
	-22÷158	°F	




T22U115B

standard with fan

> CONTACT US







T22U115B

standard with fan

> CONTACT US

