## Rittal – The System.

Faster – better – everywhere.





# SK 3237.200 Outlet filter

State: 14/12/2022 (Source: rittal.com/com-en)

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

ENCLOSURES

### SK 3237.200 - Outlet filter Standard

For ventilation by convection, an outlet filter can be fitted in both the upper and lower sections of the enclosure.



#### Features

Model No.	SK 3237.200
Product description	For ventilation by convection, an outlet filter can be installed in the upper and lower sections of the enclosure.
Material	ABS
Colour	RAL 7035
Supply includes	Outlet filter Chopped-fibre filter mat
Mounting cut-out	Cut-out width: 92 mm Cut-out height: 92 mm
Dimensions	Width: 116.5 mm Height: 116.5 mm Depth: 16 mm
Protection category NEMA	Type 12 with chopped-fibre filter/pleated filter
IP protection category to IEC 60 529	IP54 with chopped-fibre filter/pleated filter IP55 with pleated filter and absorber mat IP56 with chopped-fibre filter/pleated filter and hose-proof hood
Packs of	1 pc(s).
Weight/pack	0.12 kg
Copper weight (kg per piece)	0

#### Features

Customs tariff number	39269097
EAN	4028177651616
ETIM 7.0	EC002513
ECLASS 8.0	27180706

## Approvals

Approvals	CSA
	GOST UL + C-UL - FTTA
	UR + C-UR (recognized)
Certificates	EAC